

Link to the product: <https://www.autogate.eu/dtm-multi-piko-150-radio-receiver-1-channel-p-2161.html>



DTM MULTI PIKO 150 Radio Receiver 1-channel

Price	36.25 Euro
Number	DTM_MULTI_PIKO_150
Manufacturer	DTM

Product description

DTM MULTI PIKO 150 Radio Receiver 1-channel.

PIKO is a 1-channel receiver in a miniature housing. It is characterized by a simple operation while maintaining high functionality. Small dimensions allow installation in almost any device, and thanks to the equipment with a cable harness and a hole for the clamp band, the installation runs smoothly and quickly. The receiver is designed for cooperation with gate controllers, roller shutters and other automation devices.

Basic parameters

power supply:	12...24V AC/DC $\pm 10\%$
max current consumption:	30mA (relay on)
memory:	150 remotes with an individual number in memory. Cooperation with DTM433MHz series remotes, and in the MULTI version, with almost all remote models operating in the KeeLoq® system
operating temperature:	-20°C / +55°C
external case dimensions (width depth height):	541x30x19mm
mounting:	receiver for indoor or inside other automation enclosure mounting, IP-20

Executive elements

relay outputs (type, number, maximum load):	NO / 1 / 1A (24V AC / DC)
output mode	monostable, turn-on time 1s

Radio parameters

radio module:	integrated, superheterodyne
transmission safety:	64-bit KeeLoq®
modulation / frequency:	OOK / 433,92MHz
input impedance of antenna:	50Ω
antenna:	factory wire antenna

Functionality

user interface:	clear and simple one-button user interface with LED
remote configuration:	the ability to assign any remote control button to the receiver
deleting a single remote:	remote control presence needed

possibility to add the remote without
access to receiver button:
verification of remote controls in
memory:

easy remote control adding function
function showing the number of added
remote controls